

# miniSmartPlug

SX885ZBBB / SX885ZBLG / SX885ZBDG / SX885ZBMN / SX885ZBDR



The SALUS miniSmartPlug is small, yet powerful enough to provide simple on/off power control of devices using up to 15 A.

- Small size not only keeps the other outlet of a standard duplex receptacle clear, it also allows use of a second miniSmartPlug
- A wide range of devices can be controlled given the maximum load of 15 A
- Works with home automation systems to allow smartphones, tablets or PCs to turn on and off devices from anywhere
- Monitor and manage power consumption from the home automation system
- Extends wireless network by repeating messages
- Available in a range of colors for easy identification

SALUS NORTH AMERICA, INC.  
850 Main Street  
Redwood City, CA 94063  
(888) 387-2587 | [sales@salusinc.com](mailto:sales@salusinc.com) | [www.salusinc.com](http://www.salusinc.com)

 **SALUS**<sup>®</sup>

## Descriptions and Features

The SALUS miniSmartPlug is a smart AC power switch for lamps and appliances with the following features.

- Energy consumption measurement
- Up to 15 Amp resistive load switching
- Protocol repeater to extend the wireless network
- 5 colors:
  - SX885ZBBB Baby Blue
  - SX885ZBDG Dark Gray
  - SX885ZBDR Dusty Rose
  - SX885ZBLG Light Gray
  - SX885ZBMN Mint Green

## System Overview



## Specifications

### Controls

Multifunction Button  
On, Off and Pairing

### Indicators

White LED

### Terminals

NEMA 5-15P (Type B) plug  
NEMA 5-15R (Type B) receptacle

### Mechanical

Dimensions including plug:  
2.13" x 1.46" x 2.32", 54 x 37 x 59 cm  
Dimensions not including plug:  
2.13" x 1.46" x 1.49", 54 x 37 x 38 cm

### Power

120 VAC, +/- 10%, 60 Hz  
Max switch current: 15 A resistive  
Measurement accuracy: +/- 2% for >90 W loads

### Radio

802.15.4 radio (2.54 GHz) Zigbee HA1.2 based protocol

### Environmental Conditions

Operating: 32° -104° F, 0° - 40° C  
10 - 90% RH, non-condensing  
Storage: -4° - 140° F, -20° - 85° C  
10 - 90% RH, non-condensing

### Agency Compliance

FCC, Industry Canada  
ETL listed for UL 61010-1, UL 60730-1  
ETL listed for CAN/CSA C22.2 No. 61010-1,  
CAN/CSA E60730-1

### Warranty

5 years limited warranty

### Compatible Devices

SG888ZB Universal Gateway

**Note: Specifications are subject to change without notice**



## Order Details

Model Name: miniSmartPlug		
Model	Single Unit UPC	Carton GTIN
SX885ZBLG	817989022004	10817989022001 (48 pcs)
SX885ZBDG	817989022011	10817989022018 (48 pcs)
SX885ZBMN	817989022028	10817989022025 (48 pcs)
SX885ZBDR	817989022035	10817989022032 (48 pcs)
SX885ZBBB	817989022042	10817989022049 (48 pcs)