

The Original Since 1981

43153 Business Park Dr. Temecula, CA 92590 Email: info@falconstainless.com www.falconstainless.com TEL: (818) 767-3569 FAX: (818) 768-8533 Toll Free 1-800-814-8444



Corrugated Stainless Steel Flexible Lavatory Connectors Specification Sheet

SPECIFICATION:

Furnish and install Corrugated Stainless Steel 1/2"Lavatory, Tankless Connector

DESIGN FEATURES: Mega-flow SUPER Water-flexTM

- 304 Series Stainless Steel
- Easy Installation
- Installs without tools
- Maintains optimum flow no restriction
- Kink and Crimp Free
- Chromed brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California H & S Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

Model #	Description	Length
S-02	½" FIP x ½" FIP	12", 16", 20", 30", 36" 60"





Quantity:

